

MATERIAL SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	LOCTITE 242 THREADLOCKER
Proper Shipping Name:	None allocated.
Other Names:	THREADLOCKER 242.
Product Code(s):	135356, 135355, 1436428
Part Number(s):	24241(250 ml), 24231(50 ml),33508 (50ml)
Use:	Anaerobic adhesive.
Supplier:	HENKEL AUSTRALIA PTY. LIMITEDABN 82 001 302 996ADHESIVE TECHNOLOGIES135-141 Canterbury Road, Kilsyth, Victoria, 3137 Tel 03 9724 644424 HOUR EMERGENCY CONTACT NUMBER:Tel:1800 032 379

SECTION 2. HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE:

Hazardous according to the criteria of Safe Work Australia. This material has been classified as Irritant (Xi).

Risk phrase(s):

R36/37/38 Irritating to eyes, respiratory system and skin. R43 - May cause sensitisation by skin contact.

Safety phrase(s):

S24/25 - Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S28 - After contact with skin, wash immediately with plenty of soap suds.
S37/39 - Wear suitable gloves and eye/face protection.

S46 - If swallowed, seek medical advice immediately and show this container or label.

DANGEROUS GOODS INFORMATION:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

SUSDP POISON SCHEDULE: None allocated.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS:

CHEMICAL ENTITY	CAS NO.	PROPORTION
Polyglycol dimethacrylate	[25852-47-5]	>60% w/w
Polyglycol oleate	[9004-96-0]	10-30% w/w
Cumene hydroperoxide	[80-15-9]	1-<3% w/w
Propylene glycol	[57-55-6]	1<-5% w/w
Other ingredients determined not to be haz	ardous	to 100%



SECTION 4.	FIRST AID MEASURES
Ingestion:	If swallowed, do not induce vomiting. For advice, contact a Poisons Information Centre (Phone 13 11 26) or a doctor.
Skin:	Remove contaminated clothing and wash affected areas with plenty of water. If irritation, redness or blistering occurs, seek medical attention.
Eyes:	Hold eyes open and flush with water for at least 15 minutes. If irritation develops, seek medical attention.
Inhalation:	If inhaled, remove from contaminated area. For all but the most minor symptoms, arrange for patient to be seen by a doctor.
Advice to doctor:	Treat symptomatically.
First Aid facilities	Eye wash and normal washroom facilities. A safety shower is recommended.
SECTION 5.	FIRE FIGHTING MEASURES

Suitable extinguishing media: Use foam, dry chemical or carbon dioxide.

Hazards from combustion products: In a fire, it will char. Under fire conditions, it will release carbon monoxide, oxides of sulphurand noxious fumes.

Precautions for fire fighters and special protective equipment: If there is a risk of exposure to products of combustion, fire-fighters should wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Wear protective gloves, chemical goggles and safety boots. Wipe up residue with a cloth. For large spills contain and collect with inert absorbent materials (e.g. sand, earth, vermiculite). Transfer to sealable containers suitable for storing spilled material. Flush areas in contact with spilled material with adequate warm soapy water to render the area safe for human contact. Note: Residues are slightly water soluble. Do not contaminate watercourse. Dispose of solid residues in chemical waste disposal area in accordance with relevant State and Federal requirements.

SECTION 7. HANDLING AND STORAGE

Safe Handling: Observe recommendations made under SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION. Use in a well ventilated area. Avoid breathing vapour.

Storage: Store indoors in a cool, dry and well ventilated area. Keep containers sealed when not in use. Store in original containers away from heat, sparks and open flames. Store at or below 38°C.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National exposure standards:	TWA :10 mglm ³ as propylene glycol (particulates)
Engineering controls:	: 474 mglm ³ as propylene glycol (vapour and particulates) None required under normal conditions of use, but if vapour or mist is being generated, use a local mechanical exhaust

Personal protective equipment: Use good industrial hygiene. Avoid contact with skin and eyes. Wear overalls, neoprene or butyl rubber gloves and safety glasses with side shields. Use a well ventilated area. If inhalation risk exists, wear a respirator complying with the requirements of AS 1715 and AS 1716.



MATERIAL SAFETY DATA SHEET

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical data:

Appearance: Specific gravity: Solubility: Flash point (PMCC): VOC content: Blue liquid. 1.1 @ 24°C Slightly soluble in water > 90°C 49.3 g/l

SECTION 10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Open flames, sparks, strong heat.

Incompatible materials: Keep away from strong oxidising agents, acids and alkalies. This product is destabilised by strong reducing agents.

Hazardous decomposition products: In a fire, it can release carbon monoxide, oxides of sulphur and noxious fumes.

Hazardous reactions: Hazardous polymerisation will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

HEALTH EFFECTS:

Acute:

Ingestion:	If swallowed, may cause gastrointestinal irritation.
Skin:	Irritating to skin. May cause sensitisation by skin contact.
Eyes:	Contact with the eyes can cause severe irritation.
Inhalation:	Inhalation of vapours may cause respiratory irritation.
Chronic:	Repeated or prolonged skin contact may cause chronic dermatitis.

Toxicity information: None available for this product.

SECTION 12. ECOLOGICAL INFORMATION

Do not allow product to contaminate waterways or soil. This product may be harmful to aquatic organisms.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal of this material should be undertaken by a registered chemical disposal company. Empty containers should be disposed of according to local regulations.

SECTION 14. TRANSPORT INFORMATION

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).



MATERIAL SAFETY DATA SHEET

SECTION 15. REGULATORY INFORMATION

SUSDP POISON SCHEDULE: None allocated

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms:

SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons

Reference(s):

1. Henkel US. MSDS for LOCTITE 242, Threadlocker medium strength, May 2009

DISCLAIMER:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.